



DeVilbiss iFill® Personal Oxygen Station Model 535D

The future of home oxygen.

The iFill Personal Oxygen Station is designed to help you **convert existing oxygen customers** who rely on cylinder deliveries. As a result, you can adopt a non-delivery or limited delivery business model to **serve more patients** without adding staff or costly services.

The iFill unit extracts purified oxygen from room air using standard oxygen concentrator technology. Unlike competitive units, **iFill units can be used with your existing concentrator fleet.**

The iFill System makes it **easy and convenient** for your customers to fill portable oxygen cylinders in their homes and gives them **greater freedom** to come and go as they please.



DeVilbiss iFill Personal Oxygen Station

Performance and Design Features

- Fills M6 cylinders in just **a little over an hour** – not the two hours or more that it can take with other in-home oxygen filling units; shorter fill times save energy costs
- **Easily tops** off partially-filled cylinders
- **Automatically shuts off** when filling is complete
- Choice of cylinders – **Standard 870 Post Valve or Continuous Flow regulator**
- Simple 3-step operation
- **Fills iFill proprietary cylinders**
- Can be placed and used virtually anywhere in the home, **minimizing noise and disruption** to daily life
- **Intuitive design is easy to use** – simply align the cylinder's nipple connector with the fill connector on the unit and click into place
- Easy-roll casters make iFill **easy to move and store** when not in use
- **Control panel light** signals when cylinder is filling and when it's full
- Large cylinder release ring is **designed for individuals with limited dexterity**; requires little pressure to depress

iFill 870 Post Valve Cylinders

Can be used with most conserving devices

535D-M6-870	M6 iFill® Cylinder with 870 Post Valve
535D-C-870	C iFill® Cylinder with 870 Post Valve
535D-D-870	D iFill® Cylinder with 870 Post Valve
535D-E-870	E iFill® Cylinder with 870 Post Valve

iFill Continuous Flow Cylinders

- 0.5 to 6 lpm continuous flow
- Single lumen cannula
- Brass fittings
- No batteries required

535D-D-CF	D iFill® Cylinder with Integrated Regulator
535D-E-CF	E iFill® Cylinder with Integrated Regulator

Cylinder Specifications

Model	Fill Time (Minutes)	Weight (lbs.)	Oxygen Duration (Hours at 2 lpm + 20 bpm)
M6 870 Post	75	3.9	**
C 870 Post	130	5.4	**
D CF Regulator	215	7.0	3.5*
D 870 Post	215	7.0	**
E CF Regulator	350	9.6	5.7*
E 870 Post	350	9.4	**

* at 2 lpm

** varies dependent on regulator

iFill Packages

535D	DeVilbiss iFill® Personal Oxygen Station
535D-2M6870	iFill®, 2 M6 Cylinders with 870 Post Valve and Cylinder Carry Bag
535D-2C870	iFill®, 2 C Cylinders with 870 Post Valve and Cylinder Carry Bag
535D-2D870	iFill®, 2 D Cylinders with 870 Post Valve and Cylinder Carry Bag
535D-2E870	iFill®, 2 E Cylinders with 870 Post Valve and Cylinder Cart
535D-M6-PD-PKG	iFill®, 2 M6 Cylinders with 870 Post Valve, Electronic Conservor, and Cylinder Carry Bag
535D-2CP	iFill®, 2 C Cylinders with 870 Post Valve, Electronic Conservor, and Cylinder Carry Bag
535D-2DP	iFill®, 2 D Cylinders with 870 Post Valve, Electronic Conservor, and Cylinder Carry Bag
535D-2EP	iFill®, 2 E Cylinders with 870 Post Valve, Electronic Conservor, and Cylinder Cart
535D-2DC	iFill®, 2 D Cylinders with Integrated Regulator and Cylinder Carry Bag
535D-2EC	iFill®, 2 E Cylinders with Integrated Regulator and Cylinder Cart

Technical Specifications

Product Weight	66 lbs.
Product Dimensions	28.5" H x 12.25" W x 22.5" D
Oxygen Purity	93% +/- 3%
Sound Level	50 dBA
Filling Time	75 Minutes (M6 Cylinder)
Electrical Requirements	115V, 60 Hz, 4.1 Amps
Power Consumption	400 Watts Avg.
Cylinder Top Off	Yes
Warranty	3 years or 3000 hours – whichever comes first



DeVilbiss Healthcare | 100 DeVilbiss Drive | Somerset, PA 15501 | USA.
800.338.1988 | 814.443.4881 | www.DeVilbissHealthcare.com